

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXIT BR5F66-BladeRep Profile Filler
5
Quality No.: 4915F61163000

Revision Date 06.11.2019
Print Date 06.11.2019
Version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ALEXIT BR5F66-BladeRep Profile Filler 5 6116 grün / green
matt

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Industrial serial painting
stance/Mixture

1.3 Details of the supplier of the safety data sheet

Producer : Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Strasse 189
21107 Hamburg
Germany

Telephone : +49 (0) 40 75103 0
Telefax : +49 (0) 40 75103 375
E-mail address of person : sdb_info@umco.de
responsible for the SDS

1.4 Emergency telephone number

Emergency telephone num- : +49 (0) 551 / 19240 (Toxic agent information centre North /
ber NORD)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling

EUH210 Safety data sheet available on request.
EUH208 Contains dimethylbis[(1-oxoneodecyl)oxy]stannane. May produce an allergic
reaction.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXIT BR5F66-BladeRep Profile Filler
5
Quality No.: 4915F61163000

Revision Date 06.11.2019
Print Date 06.11.2019
Version 1

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture of synthetic resins and pigments

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
dimethylbis[(1-oxoneodecyl)oxy]stannane	68928-76-7 273-028-6 01-2120770324-57	Acute Tox. 3; H301 Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 0,0025 - < 0,025

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In all cases of doubt, or when sickness symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air, keep patient warm and at rest.
Call a doctor, should the air passages be affected
- In case of skin contact : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognised skin cleanser.
Do NOT use solvents or thinners !
- In case of eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- If swallowed : Do NOT induce vomiting.
If accidentally swallowed obtain immediate medical attention.
Never give anything by mouth to an unconscious person.
Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXIT BR5F66-BladeRep Profile Filler
5
Quality No.: 4915F61163000

Revision Date 06.11.2019
Print Date 06.11.2019
Version 1

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Not combustible under normal conditions.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters : Appropriate breathing apparatus may be required.

Further information : DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO ENTER DRAINS OR WATER COURSES!!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Take the precautions customary when handling chemicals.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Do not let product enter drains.
If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see chapter 13).
Clean preferably with a detergent; avoid use of solvents.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with the skin and the eyes.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXIT BR5F66-BladeRep Profile Filler

Revision Date 06.11.2019

5

Print Date 06.11.2019

Quality No.: 4915F61163000

Version 1

Comply with the health and safety at work laws.
Smoking, eating and drinking should be prohibited in the application area.
Observe specific national regulations for handling and use of paints.

Advice on protection against fire and explosion : No special protective measures against fire required.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information on storage conditions : Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep container dry in a cool, well-ventilated place.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

Recommended storage temperature : 5 - 35 °C

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dimethylbis[(1-oxodecyl)oxy]stannane	68928-76-7	TWA	0,1 mg/m3 (Tin)	GB EH40
Further information	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	0,2 mg/m3 (Tin)	GB EH40

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
barium sulfate	Workers	Inhalation	Long-term systemic effects	10 mg/m3



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXIT BR5F66-BladeRep Profile Filler

Revision Date 06.11.2019

5

Print Date 06.11.2019

Quality No.: 4915F61163000

Version 1

	Consumers	Inhalation	Long-term systemic effects	10 mg/m3
	Consumers	Oral	Long-term systemic effects	13000 mg/kg bw/day
.epsilon.-Caprolactone, oligomeric reaction products with propylidynetrimethanol	Workers	Inhalation	Long-term systemic effects	3,5 mg/m3
	Workers	Dermal	Long-term systemic effects	1,1 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,6 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
barium sulfate	Fresh water	115 µg/l
	Fresh water sediment	600,4 mg/kg dry weight (d.w.)
	Sewage treatment plant	62,2 mg/l
	Soil	207,7 mg/kg dry weight (d.w.)
.epsilon.-Caprolactone, oligomeric reaction products with propylidynetrimethanol	Fresh water	0,15 mg/l
	Marine water	0,015 mg/l
	Sewage treatment plant	670 mg/l

8.2 Exposure controls

Engineering measures

Provide adequate ventilation. This should be achieved by the use of local exhaust ventilation and good general extraction.

Personal protective equipment

Eye protection : Wear safety goggles to protect against splashes.

Hand protection

Remarks : Adhere to the professional organisation rule "Use of protective gloves". Appropriate chemicals resistant glove tested in compliance with EN 374.
Recommendation for protection against components generally found in the products:

For short-term contact (i.e. splash protection):

Appropriate material:

nitrile rubber, Neoprene

Material thickness: > 0,4 mm

Breakthrough time: > 480 min

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXIT BR5F66-BladeRep Profile Filler

Revision Date 06.11.2019

5

Print Date 06.11.2019

Quality No.: 4915F61163000

Version 1

Before use, the protective glove should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Preventive hand protection (skin protection cream) recommended. Wash immediately contaminated skin. Design operations thus to avoid permanent use of protective gloves.

- Skin and body protection : Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.
- Respiratory protection : None, but avoid breathing vapours if possible.
- Protective measures : Avoid product contact with skin, eyes and clothing. Avoid the inhalation of dust from sanding, particulates and spray mist arising from the application of this preparation.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : according product name
- Odour : characteristic
- Boiling point/boiling range : ca. 120 °C
- Flash point : Not applicable
- Upper explosion limit : No data available
- Lower explosion limit : No data available
- Vapour pressure : ca. 100 hPa (50 °C)
- Density : ca. 1,8 g/cm³ (20 °C)
- Solubility(ies)
Water solubility : insoluble
- Auto-ignition temperature : No data available
- Viscosity
Flow time : > 151 s
Cross section: 4 mm
Method: DIN 53211
> 101 s

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg (Wilhelmsburg)
Tel.: +49 (0) 40 / 75 10 30
Fax: +49 (0) 40 / 75 10 33 75
www.mankiewicz.de

Bank Name	Ort	Kto.-Nr.
Deutsche Bank	Hamburg	600227300
HypoVereinsbank	Hamburg	59273300
Postbank	Hamburg	373205

BLZ	BIC
200 700 00	DEUTDE33HAN
200 300 00	HYVEDE33HAN
200 100 20	PNKDEFF200

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter:
Michael O. Grau

Bureau Veritas
Certification:
ISO 9001,
TS 16949,
EN 9100



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXIT BR5F66-BladeRep Profile Filler
5
Quality No.: 4915F61163000

Revision Date 06.11.2019
Print Date 06.11.2019
Version 1

Cross section: 6 mm
Method: ISO 2431

9.2 Other information

Solvent separation : < 3 %(V)

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Stable under recommended storage and handling conditions (See section 7).

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

dimethylbis[(1-oxoneodecyl)oxy]stannane:

Acute oral toxicity : LD50 (Rat): 190 mg/kg

Skin corrosion/irritation

Components:

dimethylbis[(1-oxoneodecyl)oxy]stannane:

Species : Rabbit
Method : OECD Test Guideline 404
Result : irritating



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXIT BR5F66-BladeRep Profile Filler
5
Quality No.: 4915F61163000

Revision Date 06.11.2019
Print Date 06.11.2019
Version 1

Further information

Product:

Remarks : Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : There are no data available on the preparation itself.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: There are no data available on the preparation itself.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: There are no data available on the preparation itself.

12.4 Mobility in soil

Product:

Mobility : Remarks: There are no data available on the preparation itself.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : There are no data available on the preparation itself. The product should not be allowed to enter drains or water courses.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

MANKIEWICZ
Lackierideen der Zukunft



Commercial Product Name: ALEXIT BR5F66-BladeRep Profile Filler
5
Quality No.: 4915F61163000

Revision Date 06.11.2019
Print Date 06.11.2019
Version 1

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.
- Waste key for the unused product : 08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

- ADR : Not regulated as a dangerous good
- Remarks : If transported within the user's premises: To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

- Remarks : Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXIT BR5F66-BladeRep Profile Filler
5
Quality No.: 4915F61163000

Revision Date 06.11.2019
Print Date 06.11.2019
Version 1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Not applicable

Other regulations:

The information given in this material safety data sheet does not release the user from its duty of risk assessment and control in the work place defined in other health and safety law. Adhere to the national sanitary and occupational safety regulations when using this product.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for the mixture.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Chronic : Long-term (chronic) aquatic hazard
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - In-

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg (Wilhelmsburg)
Tel.: +49 (0) 40 / 75 10 30
Fax: +49 (0) 40 / 75 10 33 75
www.mankiewicz.de

Bank Name	Ort	Kto.-Nr.	BLZ	BIC	IBAN
Deutsche Bank	Hamburg	600227300	200 700 00	DEUTDE33HAN	DE58 2007 0000 0600 2273 00
HypoVereinsbank	Hamburg	592733000	200 300 00	HYVEDE33HAN	DE34 2003 0000 0059 2733 00
Postbank	Hamburg	373205	200 100 20	PBNKDE33HAN	DE85 2001 0020 0000 3732 05

Sitz/Registergericht Hamburg: HRA 42442
Bureau Veritas
Certification:
ISO 9001,
TS 16949,
EN 9100
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter:
Michael O. Grau



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: ALEXIT BR5F66-BladeRep Profile Filler

Revision Date 06.11.2019

5

Print Date 06.11.2019

Quality No.: 4915F61163000

Version 1

ternational Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : This safety datasheet complies with the requirements of regulation (EC) No 1907/2006(2015/830).

Department issuing safety data sheet

UMCO GmbH

Georg-Wilhelm-Str.187, D-21107 Hamburg

Telefon: +49(0)40/555 546 300 Fax: +49(0)40/555 546 357

e-mail:umco@umco.de

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN