SAFETY DATA SHEET



RELEST® Hardener PUR 1306 7,5KG

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- **1.1 Product identifier**
- : RELEST® Hardener PUR 1306 7,5KG
- Product name **Product code**
- : B-I385-1306-2075
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product is not intended for consumer use.

1.3 Details of the supplier of the safety data sheet

Akzo Nobel Hilden GmbH Düsseldorfer Str. 96 - 100 40721 Hilden Germany Tel 0049 2103 77 1 Fax +49(0)210377474 Produced by BASF Coatings GmbH, Germany

: Reach.packaging.coatings@akzonobel.com e-mail address of person responsible for this SDS

1.4 Emergency telephone number

Supplier **Telephone number** : +49 2103 510 46

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Sens. 1. H317 STOT SE 3, H335

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements Hazard pictograms



SECTION 2: Hazards identification

Hazard statements	 Flammable liquid and vapour. Harmful if inhaled. May cause an allergic skin reaction. May cause respiratory irritation.
Precautionary statements	
Prevention	: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.
Response	: IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
Storage	: Keep cool.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	: Hexamethylene diisocyanate, oligomers, hexamethylene-di-isocyanate
Supplemental label elements	: Contains isocyanates. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.

2.3 Other hazards

: No additional information.

Other hazards which do not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture			
Due du célie que dissé a sur s	l de redifier re	0/	Classification	-
Product/ingredient name	Identifiers	%	1272/2008 [CLP]	Туре
Hexamethylene diisocyanate, oligomers	EC: 500-060-2	≥75 - <90	Acute Tox. 4, H332	[1]
	CAS: 28182-81-2		Skin Sens. 1, H317 STOT SE 3, H335	
2-methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	≥10 - <25	Flam. Liq. 3, H226	[2]
hexamethylene-di-isocyanate	REACH #: 01-2119457571-37 EC: 212-485-8 CAS: 822-06-0 Index: 615-011-00-1	≥0.1 - <0.3	Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335 See Section 16 for the full	[1]
Date of issue/Date of revision	· 2017.07.11 Data of pr		text of the H statements declared above.	02 2/1

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 453/2010

SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

General	 In all cases of doubt, or when symptoms persist, seek medical attention. Never giv anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If i is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in nonallergic contact dermatitis and absorption through the skin. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitisation of the respiratory system, leading to an asthmatic condition, wheezing and tightness of the chest. Sensitised persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Repeated exposure may lead to permanent respiratory disability. Repeated or prolonged contact with irritants may cause dermatitis.

Contains Hexamethylene diisocyanate, oligomers, hexamethylene-di-isocyanate. May produce an allergic reaction.

SECTION 4: First aid measures

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures					
5.1 Extinguishing media Suitable extinguishing media	: Recommended: alcohol-resistant foam, CO ₂ , powders, water spray or mist.				
Unsuitable extinguishing media	: Do not use water jet.				
5.2 Special hazards arising f	om the substance or mixture				
Hazards from the substance or mixture	: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.				
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen, hydrogen cyanide, monomeric isocyanates.				
5.3 Advice for firefighters					
Special protective actions for fire-fighters	: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.				
Special protective equipment for fire-fighters	: Appropriate breathing apparatus may be required.				

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipm	ent and eme	ergency pro	ocedures				
For non-emergency personnel	1	Exclude sou Refer to prot	rces of ignitio ective measu	n and ventil ires listed ir	ate the area. A	void breath I 8.	ing vapo	our or mi	st.
For emergency responders	:	If specialised information i information i	l clothing is ro n Section 8 o n "For non-er	equired to d n suitable a mergency po	eal with the spil nd unsuitable n ersonnel".	lage, take naterials. S	note of a See also	any the	
6.2 Environmental precautions	:	Do not allow rivers, or sev regulations.	to enter draiı vers, inform t	ns or watero he appropri	courses. If the p ate authorities i	roduct con n accordar	taminate ice with	es lakes, local	
6.3 Methods and material for containment and cleaning up	:	Contain and earth, vermid according to contaminate One possible ethanol or is solution (5 p water (95 pa several days reached, clo	collect spillag culite or diato local regulati d area should (flammable) opropyl alcoh arts). A non-f rts). Add the until no furth se container	ge with non- maceous ea ons (see Se d be cleaned) decontami ol (50 parts lammable a same decon er reaction and dispose	combustible, al arth and place in ection 13). Place d immediately w nant comprises) and concentra ilternative is soo ntaminant to the in an unsealed of according to	osorbent m n container e in a suita vith a suitat (by volum- ated (d: 0,8 dium carbo e remnants container. o local regu	aterial e for disp ble conta ble decor e): water 80) amm nate (5 p and let Once thi ulations (e.g. sand osal ainer. Th ntaminar r (45 par nonia parts) an stand foi s stage see sect	, nt. ts), d r is tion
Date of issue/Date of revision		: 2017-07-11	Date of previo	us issue	: 2017-07-10		Version	: 3.02	4/13

SECTION 6: Accidental release measures

13).

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used.

Examination of lung function should be carried out on a regular basis on persons spraying this mixture.

	7.1 Precautions for safe handling	 Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should be taken when re-opening partly-used containers. Precautions should be taken to minimise exposure to atmospheric humidity or water. CO₂ will be formed, which, in closed containers, could result in pressurisation. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, dirnking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses. Information on fire and explosion protection Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour in all
--	-----------------------------------	--

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened

SECTION 7: Handling and storage

must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s) Recommendations

: No additional information.

Industrial sector specific solutions

: No additional information.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-methoxy-1-methylethyl acetate	EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 50 ppm 8 hours. TWA: 275 mg/m ³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 550 mg/m ³ 15 minutes.
Recommended monitoring procedures : If this product of atmosphere or B of the ventilation protective equip the following: E the assessment limit values and atmospheres - 0 of exposure to o (Workplace atm for the measure documents for r required.	ontains ingredients with exposure limits, personal, workplace biological monitoring may be required to determine the effectiveness in or other control measures and/or the necessity to use respiratory ment. Reference should be made to monitoring standards, such as uropean Standard EN 689 (Workplace atmospheres - Guidance for of exposure by inhalation to chemical agents for comparison with measurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 mospheres - General requirements for the performance of procedures ment of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available

8.2 Exposure controls

Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be exposed to any process in which this product is used.

Examination of lung function should be carried out on a regular basis on persons spraying this mixture.

Appropriate engineering controls	Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. Air-fed protective respiratory equipment must be worn by the spray operator, even when good ventilation is provided. In other operations, if local exhaust ventilation and good general extraction are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn. (See Occupational exposure controls.)
-------------------------------------	--

SECTION 8: Exposure controls/personal protection

Individual protection measures

Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Use safety eyewear designed to protect against splash of liquids.
Skin protection		
Body protection	-	Personnel should wear antistatic clothing made of natural fibres or of high- temperature-resistant synthetic fibres.
Other skin protection	-	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	By spraying: air-fed respirator. By other operations than spraying, in well ventilated areas, air-fed respirators could be replaced by a combination charcoal filter and particulate filter mask. (as filter combination A-P2)
		Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
Environmental exposure controls	:	Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance		
Physical state	1	Liquid.
Colour	÷	Not available.
Odour	÷	Not available.
Odour threshold	÷	Not applicable.
рН	1	Not applicable.
Melting point/freezing point	1	Not tested
Initial boiling point and boiling range	1	145 °C
Flash point	÷	Closed cup: 56°C
Evaporation rate	÷	Not tested
Flammability (solid, gas)	÷	Not applicable.
Upper/lower flammability or explosive limits	:	Greatest known range: Lower: 1.5% Upper: 7% (2-methoxy-1-methylethyl acetate)
Vapour pressure	:	2.7 mm Hg (0.3591 kPa) (Highest known value: 2-methoxy-1-methylethyl acetate)
Vapour density	1	> 1 (Air = 1) (Calculation method)
Density	÷	1.12 g/cm ³
Solubility(ies)	÷	Not tested
Partition coefficient: n-octanol/ water	:	Not tested

SECTION 9: Physical and chemical properties

Auto-ignition temperature	1	333 °C (Lowest known value: 2-methoxy-1-methylethyl acetate)
Decomposition temperature	1	Not tested
Viscosity	1	Not available.
Explosive properties	1	Not tested
Oxidising properties	:	Not tested

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity			
10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.	
10.2 Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).	
10.3 Possibility of hazardous reactions	:	The product reacts slowly with water, resulting in the production of carbon dioxide. In closed containers, pressure build-up could result in distortion, expansion and, in extreme cases, bursting of the container.	
10.4 Conditions to avoid	:	In a fire, hazardous decomposition products may be produced.	
10.5 Incompatible materials	:	Keep away from: oxidising agents, strong alkalis, strong acids, amines, alcohols, water. Uncontrolled exothermic reactions occur with amines and alcohols.	
10.6 Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in nonallergic contact dermatitis and absorption through the skin. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Based on the properties of the isocyanate components and considering toxicological data on similar mixtures, this mixture may cause acute irritation and/or sensitisation of the respiratory system, leading to an asthmatic condition, wheezing and tightness of the chest. Sensitised persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL. Repeated exposure may lead to permanent respiratory disability. Repeated or prolonged contact with irritants may cause dermatitis.

Contains Hexamethylene diisocyanate, oligomers, hexamethylene-di-isocyanate. May produce an allergic reaction. Acute toxicity

SECTION 11: Toxicol	ogical inform	nation				
Product/ingredient name	Res	Result		ecies	Dose	Exposure
2-methoxy-1-methylethyl	LD50 Dermal		Rabbit		>5 g/kg	-
aceiale	LD50 Oral		Rat		8532 mg/kg	-
Conclusion/Summary	: Not available.					
Acute toxicity estimates						
	Route				ATE valu	e
Inhalation (vapours) Inhalation (dusts and mists)	Inhalation (vapours)13,78 mg/lInhalation (dusts and mists)1,866 mg/l					
Irritation/Corrosion						
Conclusion/Summary	: Not available.					
Sensitisation						
Product/ingredient name	Route of exposure	Spe	cies		Res	sult
hexamethylene-di- isocyanate	skin	Guinea pig			Sensitising	
Conclusion/Summary	: Not available.					
<u>Mutagenicity</u>						
Conclusion/Summary	: Not available.					
Carcinogenicity						
Conclusion/Summary	: Not available.					
Reproductive toxicity						
Conclusion/Summary	: Not available.					
Teratogenicity						

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hexamethylene diisocyanate, oligomers	Category 3	Not applicable.	Respiratory tract irritation
hexamethylene-di-isocyanate	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Other information

: No additional information.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

Product/ingredient name	Result	Species	Exposure
hexamethylene-di- isocyanate	Acute EC50 >77.4 mg/l	Algae - Desmodesmus subspicatus	72 hours
	Acute EC50 >89.1 mg/l Acute LC50 >82.8 mg/l	Daphnia - Daphnia magna Fish - Brachydanio rerio	48 hours 96 hours
Conclusion/Summary	: Not available.	· · · · ·	·

12.2 Persistence and degradability

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Hexamethylene diisocyanate, oligomers	5,54	367,7	low
2-methoxy-1-methylethyl acetate	1,2	-	low
hexamethylene-di- isocyanate	0,02	57,63	low

12.4 Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PB	I and vPvB assessment
PBT	: Not applicable
vPvB	: Not applicable

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	 Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 91/689/EEC.

SECTION 13: Dispo	sal consider	ations
Disposal considerations	: Do not allow be neutralise Dispose of w If this produc longer apply For further ir	to enter drains or watercourses. Residues in empty containers should ed with a decontaminant (see section 6). /aste according to applicable legislation. ct is mixed with other wastes, the original waste product code may no and the appropriate code should be assigned. nformation, contact your local waste authority.
Waste code		Waste designation
08 01 12	waste paint and v	arnish other than those mentioned in 08 01 11
Packaging		
Methods of disposal	: The generati packaging sl when recycli	ion of waste should be avoided or minimised wherever possible. Waste hould be recycled. Incineration or landfill should only be considered ng is not feasible.
Disposal considerations	: Using inform the relevant Empty conta Dispose of c national lega	ation provided in this safety data sheet, advice should be obtained from waste authority on the classification of empty containers. iners must be scrapped or reconditioned. containers contaminated by the product in accordance with local or al provisions.
Type of packaging		European waste catalogue (EWC)
CEPE Paint Guidelines	15 01 10*	packaging containing residues of or contaminated by dangerous substances
Special precautions	: This materia taken when I Empty conta residues ma container. D thoroughly ir soil, waterwa	I and its container must be disposed of in a safe way. Care should be handling emptied containers that have not been cleaned or rinsed out. iners or liners may retain some product residues. Vapour from product y create a highly flammable or explosive atmosphere inside the the bo not cut, weld or grind used containers unless they have been cleaned internally. Avoid dispersal of spilt material and runoff and contact with avs, drains and sewers.

SECTION 14: Transport information

ADR/RID	ADN	IMDG	ΙΑΤΑ
UN1866	UN1866	UN1866	UN1866
Resin solution, flammable	Resin solution, flammable	Resin solution, flammable	Resin solution, flammable
3	3	3	3
111	111	111	111
No.	No.	No.	No.
Special provisions 640 (E) Tunnel code	-	-	-
	ADR/RID UN1866 Resin solution, flammable 3 3 JIII No. Special provisions 640 (E) Tunnel code (D/E)	ADR/RIDADNUN1866UN1866Resin solution, flammableResin solution, flammable33IIIIIINo.No.Special provisions 640 (E)-Tunnel code (D/E)-	ADR/RIDADNIMDGUN1866UN1866UN1866Resin solution, flammableResin solution, flammableResin solution, flammable333IIIIIIIIINo.No.No.Special provisions 640 (E)-Tunnel code (D/E)-

SECTION 14: Transport information

14.7 Transport in bulk	: Not applicable
according to Annex II of	
MARPOL 73/78 and the IBC	
Code	

SECTION 15: Regulatory information 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorisation Annex XIV None of the components are listed. Substances of very high concern None of the components are listed. Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Other EU regulations VOC for Ready-for-Use : Not available. **Mixture** : All components are listed or exempted. **Europe inventory**

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria						
Category	Category					
P5c: Flammable liquids	s 2 and 3 not falling under P5a or P5b					
Industrial use	: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.					
15.2 Chemical Safety Assessment	: No Chemical Safety Assessment has been carried out.					
SECTION 16: Othe	er information					
Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]					

Date of issue/Date of revision	: 2017-07-11	Date of previous issue	: 2017-07-10	Version : 3.02

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic

12/13

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

SECTION 16: Other information

	PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative			
Full text of abbreviated H : statements	H226 H315 H317 H319 H331 H332 H332 (inhalation) H334 H335	Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic if inhaled. Harmful if inhaled. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.		
Full text of classifications : [CLP/GHS]	Acute Tox. 3, H331 Acute Tox. 4, H332 Eye Irrit. 2, H319 Flam. Liq. 3, H226 Resp. Sens. 1, H334 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335	ACUTE TOXICITY (inhalation) - Category 3 ACUTE TOXICITY (inhalation) - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 3 RESPIRATORY SENSITIZATION - Category 1 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3		
Date of printing :	2017-07-11			
Date of issue/ Date of : revision	2017-07-11			
Date of previous issue :	2017-07-10			
Version :	3.02			

Notice to reader

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.