SAFETY DATA SHEET



RELEST® Wind Putty Porefiller

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : RELEST® Wind Putty Porefiller

Product code : B-I372-5615-2066

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product is not intended for consumer use.

1.3 Details of the supplier of the safety data sheet

Akzo Nobel Hilden GmbH Düsseldorfer Str. 96 - 100 40721 Hilden Germany Tel 0049 2103 77 1 Fax +49(0)210377474 Produced by BASF Coatings GmbH, Germany

e-mail address of person : psra.wfa.emea@akzonobel.com

responsible for this SDS

1.4 Emergency telephone number

Supplier

Telephone number : +49 2103 510 46

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word : Warning

Hazard statements: Causes serious eye irritation.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

Precautionary statements

Date of issue/Date of revision : 2018-06-08 Date of previous issue : 2018-06-08 Version : 2.34 1/11

RELEST® Wind Putty Porefiller

SECTION 2: Hazards identification

Prevention

: Wear protective gloves. Wear eye or face protection. Avoid release to the environment.

Response

: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

: Not applicable.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients
Supplemental label

: tetraethylN,N'-(methylenedicyclohexane-4,1-diyl)bis-dl-aspartate, diethyl fumarate

Supplemental label elements

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous

: Not applicable.

substances, mixtures and articles

2.3 Other hazards

Other hazards which do not result in classification

: No additional information.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Classification Regulation (EC) No. 1272/2008 [CLP] | Туре |
|--|---|-----------|---|------|
| tetraethylN,N'- (methylenedicyclohexane-4, 1-diyl)bis-dl-aspartate | EC: 429-270-1 | ≥50 - <75 | Skin Sens. 1, H317 | [1] |
| | CAS: 136210-30-5 Index: 607-521-00-8 | | Aquatic Chronic 3, H412 | |
| diethyl fumarate | EC: 210-819-7 CAS: 623-91-6 | ≥1 - <3 | Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 2, H411 | [1] |
| | | | See Section 16 for the full text of the H statements declared above. | |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision : 2018-06-08 Date of previous issue : 2018-06-08 Version : 2.34 2/11

Inhalation

SECTION 4: First aid measures

4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery

position and seek medical advice.

position and seek medical advice.

Eye contact: Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion: If swallowed, seek medical advice immediately and show the container or label.

Keep person warm and at rest. Do NOT induce vomiting.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear

gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains tetraethylN,N'-(methylenedicyclohexane-4,1-diyl)bis-dl-aspartate. May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing : Recommended: alcohol-resistant foam, CO₂, powders, water spray. media

Unsuitable extinguishing: Do not use water jet.

media

Date of issue/Date of revision : 2018-06-08 Date of previous issue : 2018-06-08 Version : 2.34 3/11

SECTION 5: Firefighting measures

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

- **Hazardous thermal**
- : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
- decomposition products
- : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

Special protective actions for fire-fighters

- : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
- Special protective equipment for fire-fighters
- : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

- For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- 6.2 Environmental precautions
- : Do not allow to enter drains or watercourses. If the product contaminates lakes. rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
- 6.3 Methods and material for containment and cleaning up
- : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.
- 6.4 Reference to other sections
- : See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- : Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
 - Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Date of issue/Date of revision : 2018-06-08 Date of previous issue : 2018-06-08 Version: 2.34

SECTION 7: Handling and storage

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Recommendations **Industrial sector specific** solutions

: No additional information. : No additional information.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available

Date of issue/Date of revision : 2018-06-08 Date of previous issue : 2018-06-08 Version: 2.34

SECTION 8: Exposure controls/personal protection

8.2 Exposure controls

Appropriate engineering controls

: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Skin protection

Body protection

: Use safety eyewear designed to protect against splash of liquids.

: Personnel should wear antistatic clothing made of natural fibres or of high-

: Wear a respirator conforming to EN140 with Type A/P2 filter or better.

temperature-resistant synthetic fibres.

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection

Other skin protection

nmental exposure : Do not allow to enter drains or watercourses.

Environmental exposure

controls

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Colour : Not available.

Odour : Not available.

Odour threshold : Not applicable.

PH : Not applicable.

Melting point/freezing point : Not tested

Initial boiling point and : 300 °C

boiling range

Flash point : Closed cup: 100°C

Evaporation rate : Not tested **Flammability (solid, gas)** : Not applicable.

Upper/lower flammability or

explosive limits

: Not applicable. [Not considered to be flammable .]

Vapour pressure : Not applicable.

Vapour density : > 1 (Air = 1) (Calculation method)

Density : 1.42 g/cm³
Solubility(ies) : Not tested
Partition coefficient: n-octanol/ : Not tested

water

Auto-ignition temperature : 375 °C (Lowest known value: tetraethylN,N'-(methylenedicyclohexane-4,1-diyl)

bis-dl-aspartate)

Date of issue/Date of revision : 2018-06-08 Date of previous issue : 2018-06-08 Version : 2.34 6/11

RELEST® Wind Putty Porefiller

SECTION 9: Physical and chemical properties

Decomposition temperature: Not testedViscosity: > 684.3 mm2/sExplosive properties: Not testedOxidising properties: Not tested

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur.hazardous reactions

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition

products.

10.5 Incompatible materials: Keep away from the following materials to prevent strong exothermic reactions:

oxidising agents, strong alkalis, strong acids.

10.6 HazardousUnder normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains tetraethylN,N'-(methylenedicyclohexane-4,1-diyl)bis-dl-aspartate. May produce an allergic reaction.

Acute toxicity

Conclusion/Summary: Not available.

Acute toxicity estimates

| Route | ATE value |
|-------|-------------|
| Oral | 30137 mg/kg |

Date of issue/Date of revision: 2018-06-08Date of previous issue: 2018-06-08Version: 2.347/11

RELEST® Wind Putty Porefiller

SECTION 11: Toxicological information

Irritation/Corrosion

Conclusion/Summary: Not available.

Sensitisation

Conclusion/Summary: Not available.

Mutagenicity

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary: Not available.

Reproductive toxicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|------------------------------|
| diethyl fumarate | Category 3 | Not applicable. | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Other information : No additional information.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

Conclusion/Summary: Not available.

12.2 Persistence and degradability

12.3 Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|--|--------|------|-----------|
| tetraethylN,N'- (methylenedicyclohexane-4, 1-diyl)bis-dl-aspartate | 5,16 | 0,25 | low |

12.4 Mobility in soil

Soil/water partition : Not available.

coefficient (Koc)

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

Date of issue/Date of revision : 2018-06-08 Date of previous issue : 2018-06-08 Version : 2.34 8/11

RELEST® Wind Putty Porefiller

SECTION 12: Ecological information

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: Yes.

Disposal considerations

: Do not allow to enter drains or watercourses.

Dispose of waste according to applicable legislation.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

| Waste code | Waste designation |
|------------|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other dangerous substances |

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations

: Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions.

| Type of packaging | | European waste catalogue (EWC) |
|-----------------------|-----------|--|
| CEPE Paint Guidelines | 15 01 10* | packaging containing residues of or contaminated by dangerous substances |

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

Date of issue/Date of revision : 2018-06-08 Date of previous issue : 2018-06-08 Version : 2.34 9/11

RELEST® Wind Putty Porefiller

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | IATA |
|------------------------------------|----------------|----------------|----------------|----------------|
| 14.1 UN number | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - | - | - |
| 14.3 Transport hazard class(es) | - | - | - | - |
| 14.4 Packing group | - | - | - | - |
| 14.5 Environmental hazards | No. | No. | No. | No. |
| Additional information | - | - | - | - |

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

VOC for Ready-for-Use : Not available.

Mixture

: Not determined. **Europe inventory**

Seveso Directive

This product is not controlled under the Seveso Directive.

Date of issue/Date of revision : 2018-06-08 Date of previous issue : 2018-06-08 Version: 2.34 10/11

SECTION 15: Regulatory information

Industrial use

: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

15.2 Chemical Safety Assessment

: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Full text of abbreviated H statements

| : | H302 | Harmful if swallowed. |
|---|------|--|
| | H315 | Causes skin irritation. |
| | H317 | May cause an allergic skin reaction. |
| | H318 | Causes serious eye damage. |
| | H319 | Causes serious eye irritation. |
| | H335 | May cause respiratory irritation. |
| | | Toxic to aquatic life with long lasting effects. |
| | H412 | Harmful to aquatic life with long lasting effects. |
| | | |

Full text of classifications [CLP/GHS]

Acute Tox. 4, H302 ACUTE TOXICITY (oral) - Category 4 Aquatic Chronic 2, H411 LONG-TERM AQUATIC HAZARD - Category 2 Aquatic Chronic 3, H412 LONG-TERM AQUATIC HAZARD - Category 3 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category Eve Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category SKIN CORROSION/IRRITATION - Category 2 Skin Irrit. 2, H315 Skin Sens. 1. H317 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE STOT SE 3, H335 EXPOSURE) (Respiratory tract irritation) - Category 3

Date of printing

Date of issue/ Date of

Date of previous issue

revision

: 2018-06-08 : 2018-06-08

: 2018-06-08

Version : 2.34

Notice to reader

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.

Date of issue/Date of revision : 2018-06-08 Date of previous issue : 2018-06-08 Version : 2.34 11/11