

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 12.10.2018

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Bergopur-Aqua-Decklack 6D974-R, RAL7035

Product group: Produkt

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

pigmented topcoat

1.3. Details of the supplier of the safety data sheet

Company name:	Bergolin GmbH & Co. KG	
Street:	Sachsenring 1	
Place:	D-27711 Osterholz-Scharmbeck	
Telephone:	+49 4795 95899 0	Telefax: 04795-95899-170
e-mail:	info@bergolin.de	
Contact person:	M. Gloede	Telephone: +49 541 93701-22
e-mail:	sdb@bergolin.de	
Internet:	www.bergolin.de	
Responsible Department:	Sicherheitsdatenblattverwaltung	

1.4. Emergency telephone

+49 4795 95899 0

number:

Only available during office hours. (8-16 CET)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful to aquatic life with long lasting effects.

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

Special labelling of certain mixtures

EUH208 Contains Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Acrylate copolymer dispersion

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 12.10.2018

Page 2 of 11

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
25322-69-4	polypropylene glycol			1 - < 5 %
	Acute Tox. 4; H302			
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve			1 - < 5 %
	203-905-0	603-014-00-0		
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H332 H312 H302 H315 H319			
34590-94-8	dipropylene glycol methyl ether			1 - < 5 %
	252-104-2		01-2119450011-60	
	Aromatic hydrocarbon mixture			1 - < 5 %
	265-199-0		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
41556-26-7	Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate			< 1 %
	255-437-1			
	Skin Sens. 1, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1; H317 H400 H410			
82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate			< 1 %
	280-060-4			
	Skin Sens. 1, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1; H317 H400 H410			
1415316-96-9	Fatty acids, sunflower-oil, conjugated, maleated, reaction products with diethanolamine, maleated talloil fatty acids and triethanolamine			< 1 %
			01-2120770262-59	
	Skin Sens. 1, Aquatic Chronic 3; H317 H412			
108-01-0	2-dimethylaminoethanol, N,N-dimethylethanolamine			< 1 %
	203-542-8		01-2119492298-24	
	Flam. Liq. 3, Acute Tox. 3, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1B, STOT SE 3; H226 H331 H312 H302 H314 H335			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.
Never give anything by mouth to an unconscious person or a person with cramps.
If unconscious place in recovery position and seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.

After contact with skin

Immediately remove any contaminated clothing, shoes or stockings.
After contact with skin, wash immediately with plenty of water and soap.
Do not wash with: Solvents/Thinner.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 12.10.2018

Page 3 of 11

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.
Put victim at rest, cover with a blanket and keep warm.
Do NOT induce vomiting.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water mist

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.
Hazardous decomposition products: carbon black. Health hazard.
Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition - No smoking. Ventilate affected area.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Safe handling: see section 7
Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
Collect in closed and suitable containers for disposal. Disposal: see section 13
Clean with detergents. Avoid solvent cleaners.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Solvent:

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Only use the material in places where open light, fire and other flammable sources can be kept away. Use explosion-proof electrical equipment. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Use only antistatically equipped (spark-free) tools.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink, smoke, sniff.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 12.10.2018

Page 4 of 11

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

Advice on protection against fire and explosion

Solvent - Vapours are heavier than air, spread along floors and form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in accordance with: Betriebssicherheitsverordnung (BetrSichV).

Hints on joint storage

Do not store together with: Oxidizing agent, Strong acid, Strong alkali

Further information on storage conditions

Notice the directions for use on the label.

Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
34590-94-8	(2-methoxymethylethoxy) propanol	50	308		TWA (8 h)	WEL
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL
108-01-0	2-Dimethylaminoethanol	2	7.4		TWA (8 h)	WEL
		6	22		STEL (15 min)	WEL
7727-43-7	Barium sulphate, inhalable dust	-	10		TWA (8 h)	WEL
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol	urine	Post shift

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 12.10.2018

Page 5 of 11

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
13463-67-7	Titanium dioxide			
Worker DNEL, long-term	inhalation	local	10 mg/m ³	
Consumer DNEL, long-term	oral	systemic	700 mg/kg bw/day	
7727-43-7	barium sulfate			
Worker DNEL, long-term	inhalation	systemic	10 mg/m ³	
Worker DNEL, long-term	inhalation	local	10 mg/m ³	
Consumer DNEL, long-term	inhalation	systemic	10 mg/m ³	
Consumer DNEL, long-term	oral	systemic	13000 mg/kg bw/day	
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve			
Worker DNEL, acute	dermal	systemic	89 mg/kg bw/day	
Worker DNEL, acute	inhalation	systemic	135 mg/m ³	
Worker DNEL, acute	inhalation	local	50 mg/m ³	
Worker DNEL, long-term	inhalation	systemic	20 mg/m ³	
Worker DNEL, long-term	dermal	systemic	75 mg/kg bw/day	
Consumer DNEL, acute	dermal	systemic	44,5 mg/kg bw/day	
Consumer DNEL, acute	inhalation	systemic	426 mg/m ³	
Consumer DNEL, acute	oral	systemic	13,4 mg/kg bw/day	
Consumer DNEL, acute	inhalation	local	123 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	38 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	49 mg/m ³	
Consumer DNEL, long-term	oral	systemic	3,2 mg/kg bw/day	
34590-94-8	dipropylene glycol methyl ether			
Worker DNEL, long-term	dermal	systemic	65 mg/kg bw/day	
Worker DNEL, long-term	inhalation	systemic	310 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	15 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	1,67 mg/kg bw/day	
64742-95-6	Aromatic hydrocarbon mixture			
Consumer DNEL, long-term	inhalation	systemic	32 mg/m ³	
Consumer DNEL, long-term	dermal	systemic	11 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	11 mg/kg bw/day	
Worker DNEL, long-term	dermal	systemic	25 mg/kg bw/day	
Worker DNEL, long-term	inhalation	systemic	150 mg/m ³	
108-01-0	2-dimethylaminoethanol, N,N-dimethylethanolamine			
Worker DNEL, long-term	inhalation	systemic	7,4 mg/m ³	
Worker DNEL, acute	inhalation	systemic	22 mg/m ³	
Worker DNEL, long-term	inhalation	local	7,4 mg/m ³	
Worker DNEL, acute	inhalation	local	22 mg/m ³	

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 12.10.2018

Page 6 of 11

Worker DNEL, long-term	dermal	systemic	1,04 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	5 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmental compartment		Value
7727-43-7	barium sulfate	
Freshwater		0,115 mg/l
Freshwater sediment		600,4 mg/kg
Soil		207,7 mg/kg
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve	
Freshwater		8,8 mg/l
Marine water		0,88 mg/l
Freshwater sediment		34,6 mg/kg
Marine sediment		3,46 mg/kg
34590-94-8	dipropylene glycol methyl ether	
Freshwater		19 mg/l
Freshwater (intermittent releases)		190 mg/l
Marine water		1,9 mg/l
Freshwater sediment		70,2 mg/kg
Marine sediment		7,02 mg/kg
Micro-organisms in sewage treatment plants (STP)		4168 mg/l
Soil		2,74 mg/kg
108-01-0	2-dimethylaminoethanol, N,N-dimethylethanolamine	
Freshwater		0,0661 mg/l
Marine water		0,00661 mg/l
Freshwater sediment		0,0529 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,0177 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Eye/face protection

Wear eye protection/face protection.

Hand protection

Wear protective gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the wear time limits as specified by the manufacturer.

Suitable material: butyl rubber or Viton (necessarily consider the permanence of the material and See information supplied by the manufacturer.

Breakthrough time (maximum wearing time): ____ min.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 12.10.2018

Page 7 of 11

Use protective skin cream before handling the product.

Skin protection

Wear anti-static footwear and clothing Suitable material: Natural fibres (e.g. cotton) / heat-resistant synthetic fibres.

Respiratory protection

Respiratory protection necessary at: Spray application exceeding exposure limit values.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	grey
Odour:	characteristic

Test method

Changes in the physical state

Initial boiling point and boiling range:	100 °C
Flash point:	65 °C DIN 53213
Lower explosion limits:	
Upper explosion limits:	
Ignition temperature:	270 °C
Density (at 20 °C):	1,37 g/cm ³ DIN 53217
Flow time: (at 20 °C)	> 100
Solvent separation test:	<3 % (Land transport (ADR/RID))
Solvent content:	9,35 %, water: 29,70 %

9.2. Other information

Solid content:	60,95 %
----------------	---------

SECTION 10: Stability and reactivity

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidizing agent, Strong acid, Strong alkali

10.4. Conditions to avoid

May form hazardous decomposition products when exposed to high temperatures.

10.6. Hazardous decomposition products

Nitrogen oxides (NOx), carbon black, Carbon dioxide (CO₂), Carbon monoxide

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 12.10.2018

Page 8 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
25322-69-4	polypropylene glycol				
	oral	ATE 500 mg/kg			
	dermal	LD50 20100 mg/kg	Kaninchen		
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve				
	oral	LD50 470 mg/kg	Rat		
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation aerosol	ATE 1,5 mg/l			
34590-94-8	dipropylene glycol methyl ether				
	oral	LD50 5140 mg/kg	Ratte		
	dermal	LD50 9510 mg/kg	Kaninchen		
64742-95-6	Aromatic hydrocarbon mixture				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		
	inhalation (4 h) aerosol	LC50 >7,6 mg/l	Rat		
108-01-0	2-dimethylaminoethanol, N,N-dimethylethanolamine				
	oral	LD50 1190 mg/kg	Rat		
	dermal	LD50 1220 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 1641 mg/l	Rat		
	inhalation aerosol	ATE 0,5 mg/l			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.
May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience

Observations relevant to classification

Following inhalation:

Adverse human health effects and symptoms: May cause respiratory irritation. May cause damage to liver if

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 12.10.2018

Page 9 of 11

inhaled. May cause damage to kidneys if inhaled. Depression of central nervous system.
Symptoms: Headache, Dizziness, Drowsiness, Unconsciousness

After eye contact:
Irritating to eyes. (reversible.)

Following skin contact:
May be absorbed through the skin. Frequently or prolonged contact with skin may cause dermal irritation. Has degreasing effect on the skin.

Further information

There are no data available on the mixture itself.
The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve					
	Acute fish toxicity	LC50 1490 mg/l	96 h	Lepomis macrochirus		
34590-94-8	dipropylene glycol methyl ether					
	Acute fish toxicity	LC50 >1000 mg/l	96 h	Poecilia reticulata		
	Acute algae toxicity	ErC50 >969 mg/l	96 h	Pseudokirchnerella subcapitata		
	Acute crustacea toxicity	EC50 1930 mg/l	48 h	Acartia tonsa		
	Algae toxicity	NOEC 969 mg/l	3 d	Pseudokirchnerella subcapitata		
	Crustacea toxicity	NOEC 1000 mg/l	2 d	Acartia tonsa		
64742-95-6	Aromatic hydrocarbon mixture					
	Acute fish toxicity	LC50 10 mg/l	96 h	Oncorhynchus mykiss		
	Acute algae toxicity	ErC50 3,7 mg/l	96 h	Pseudokirchnerella subcapitata		
	Acute crustacea toxicity	EC50 12 mg/l	48 h	Daphnia magna		
41556-26-7	Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate					
	Acute fish toxicity	LC50 0,97 mg/l	96 h	Lepomis macrochirus (Bluegill)		OECD 203
82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate					
	Acute fish toxicity	LC50 0,9 mg/l	96 h	Brachydanio rerio (zebra-fish)		OECD 203
108-01-0	2-dimethylaminoethanol, N,N-dimethylethanolamine					
	Acute fish toxicity	LC50 146,63 mg/l	96 h	Leuciscus idus (golden orfe)		
	Acute algae toxicity	ErC50 34,47 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 98,37 mg/l	48 h	Daphnia magna (Big water flea)		
	Acute bacteria toxicity	(>1000 mg/l)	0,5 h			

12.2. Persistence and degradability

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 12.10.2018

Page 10 of 11

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
34590-94-8	dipropylene glycol methyl ether			
	OECD Guideline 301 F (Manometric Respirometry Tes)	75%	10	
	readily biodegradable			
64742-95-6	Aromatic hydrocarbon mixture			
	OECD Guideline 301 F (Manometric Respirometry Tes)	77,05%	28	
	readily biodegradable			
108-01-0	2-dimethylaminoethanol, N,N-dimethylethanolamine			
		>60	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
25322-69-4	polypropylene glycol	0,01
111-76-2	2-butoxyethanol; ethyleneglycol monobutyl ether; butyl cellosolve	0,81 (25°C)

BCF

CAS No	Chemical name	BCF	Species	Source
64742-95-6	Aromatic hydrocarbon mixture	102500	modelled data	Computer model

Further information

There are no data available on the mixture itself.
Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains.
Recycle according to official regulations.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled.
Recycle according to official regulations.

SECTION 14: Transport information

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Safety Data Sheet

according to Regulation (EC) No 1907/2006



Bergopur-Aqua-Decklack 6D974-R, RAL7035

Revision date: 12.10.2018

Page 11 of 11

Restrictions on use (REACH, annex XVII):

Entry 28: Aromatic hydrocarbon mixture

2010/75/EU (VOC): 7,623 % (104,441 g/l)

2004/42/EC (VOC): 7,623 % (104,441 g/l)

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Observe in addition any national regulations!

SECTION 16: Other information

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains Bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)