

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

SC-4 Silicone Grease Spray

Product no.

19285

REACH registration number

Not applicable

Other means of identification

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Lubricant

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

ITW Spraytec Nordic

Priorsvej 36

8600 Silkeborg

Tlf.: +45 86 82 64 44

SDS info.: www.itwinfo.dk

Contact person

Kundeservice: tlf 8682 6444

E-mail

info@itw-spraytec.dk

SDS date

31-07-2015

SDS Version

1.0

1.4. Emergency telephone number

Use your national or local emergency number

See section 4 "First aid measures"

SECTION 2: Hazards identification

▼ 2.1. Classification of the substance or mixture

Aerosol 1; H229

Aerosol 1; H222

Skin Irrit. 2; H315

Aquatic Chronic 3; H412

See full text of H-phrases in section 2.2.

2.2. Label elements

Hazard pictogram(s)**▼ Signal word**

Danger

▼ Hazard statement(s)

Pressurised container: May burst if heated. (H229)
 Extremely flammable aerosol. (H222)
 Causes skin irritation. (H315)
 Harmful to aquatic life with long lasting effects. (H412)

Safety statement(s)	General	-
	Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210). Do not spray on an open flame or other ignition source. (P211). Do not pierce or burn, even after use. (P251). Use only outdoors or in a well-ventilated area. (P271). Wear protective gloves/protective clothing. (P280).
	Response	-
	Storage	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412).
	Disposal	-

Identity of the substances primarily responsible for the major health hazards

-

2.3. Other hazards

This product contains an organic solvent. Repeated exposure to organic solvents can result in damage to the nervous system and inner organs, such as the liver and kidneys.

Additional labelling

-

Additional warnings

-

VOC

-

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances/Mixtures

NAME: cyclopentane
 IDENTIFICATION NOS.: CAS-no: 287-92-3 EC-no: 206-016-6 Index-no: 601-030-00-2
 CONTENT: 25-40%
 CLP CLASSIFICATION: Flam. Liq. 2, Aquatic Chronic 3
 H225, H412
 NOTE: S

NAME: Petroleum gases, liquefied (<0,1 % w/w 1,3-butadiene (EINECS No. 203-450-8))
 IDENTIFICATION NOS.: CAS-no: 68476-85-7 EC-no: 270-704-2 Index-no: 649-202-00-6
 CONTENT: 15-25%
 CLP CLASSIFICATION: Comp. Gas, Flam. Gas 1
 H220, H280

NAME: Naphtha (petroleum), hydrotreated light (<0,1 % w/w benzene (EINECS No 200-753-7)).
 IDENTIFICATION NOS.: CAS-no: 64742-49-0 EC-no: 265-151-9 Index-no: 649-328-00-1
 CONTENT: 15-25%
 CLP CLASSIFICATION: Flam. Liq. 2, STOT SE 3, Skin Irrit. 2, Asp. Tox. 1, Aquatic Chronic 2
 H225, H304, H315, H336, H411

(*) See full text of H-phrases in chapter 16. Occupational exposure limits are listed in section 8, if these are available.
 S = Organic solvent

Other informations

Skin Cat. 2 Sum = Sum(Ci/S(G)CLi) = 1,5176 - 2,2764
 N chronic (CAT 3) Sum = Sum(Ci/M(chronic))*25*0.1*10^CATi) = 7,19744 - 10,79616

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.
 Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give

an unconscious person water or similar.

Inhalation

Get the person into fresh air and stay with them.

Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. If irritation continues, contact a doctor.

Ingestion

Give the person plenty to drink and stay with the person. If the person feels unwell, contact a doctor immediately and take this safety data sheet or the label from the product with you. Do not induce vomiting unless recommended by the doctor. Hold head facing down so that no vomit runs back into the mouth and throat.

Burns

Rinse with water until the pain stops and continue for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc.

Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

4.3. Indication of any immediate medical attention and special treatment needed

No special

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, as in the case of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in thick black smoke. Exposure to catabolic products can damage your health. Fire fighters should use proper protection gear. Closed containers, which are exposed to fire, should be cooled with water. Do not let fire-extinguishing water run into sewers and other water courses.

Aerosols may explode if heated / fire.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stores that have not ignited must be cooled by water mist. Where possible, remove flammable materials. Make sure there is sufficient ventilation.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of a leakage to the surroundings, contact the local environmental authorities. Consider putting up waste collecting trays/basins to prevent leakage to the surroundings.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

6.4. Reference to other sections

See section on "Disposal considerations" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Consider putting up waste collecting trays/basins to prevent leakage to the surroundings. See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original. Must be stored in a cool and ventilated area, away from possible sources of combustion.

Storage temperature

< 50°C

7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

▼ OEL

Petroleum gases, liquefied (<0,1 % w/w 1,3-butadiene (EINECS... (EH40, 2005)
Long-term exposure limit (8-hour TWA reference period): 1000 ppm | 1750 mg/m³
Short-term exposure limit (15-minute reference period): 1250 ppm | 2180 mg/m³
Comments: Carc (> 0,1%butadien) (Carc = Capable of causing cancer.)

DNEL / PNEC

DNEL (Naphtha (petroleum), hydrotreated light (<0,1 % w/w benzene (EINECS No 200-753-7)).): 447 mg/m³ - Exposure: Inhalation - Duration: Long term – Systemic effects - General population
DNEL (Naphtha (petroleum), hydrotreated light (<0,1 % w/w benzene (EINECS No 200-753-7)).): 2085 mg/m³ - Exposure: Inhalation - Duration: Long term – Systemic effects - Workers

8.2. Exposure controls

Compliance with the stated exposure limits values should be checked on a regular basis.

General recommendations

▼ Observe general occupational hygiene.

Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

Exposure limits

Trade users are covered by the rules of the working environment legislation on maximum concentrations for exposure. See work hygiene threshold values below.

Appropriate technical measures

Airborne gas and dust concentrations must be kept as low as possible and below the current threshold values (see below). Use for example an exhaust system if the normal air flow in the work room is not sufficient. Make sure that eyewash and emergency showers are clearly marked.

Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

Respiratory protection is not normally required in well-ventilated areas. In case of inadequate ventilation a respirator with filter A2 is recommended.

Skin protection

Special work clothing should be used.

Hand protection

Recommended: Nitrile rubber. . See the manufacturer's instructions

Eye protection

Use face shield. Use safety glasses with a side shield as an alternative.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Colour	Odour	pH	Viscosity	Density (g/cm ³)
Aerosol	Clear	None	-	-	-

Phase changes

Melting point (°C)	Boiling point (°C)	Vapour pressure (mm Hg)
-	-	-

Data on fire and explosion hazards

Flashpoint (°C)	Ignition (°C)	Self ignition (°C)
<0	-	-

Explosion limits (Vol %)	Oxidizing properties
-	-

Solubility

Solubility in water	n-octanol/water coefficient
Insoluble	-

9.2. Other information

Solubility in fat	Additional information
-	N/A

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Avoid static electricity.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reductants agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance	Species	Test	Route of exposure	Result
Naphtha (petroleum), hydrotrea...	Rabbit	LD50	Dermal	> 2000 mg/kg
Naphtha (petroleum), hydrotrea...	Rat	LD50	Oral	> 5000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

No data available.

Respiratory or skin sensitisation

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

Long term effects

Neurotoxic effect: This product contains organic solvents, which can have an effect on the nervous system. Symptoms of neurotoxicity can be: loss of appetite, headache, dizziness, whistling in the ears, tingling sensations in the skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer. The skin will then be more prone to absorb dangerous substances, e.g. allergens.

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

SECTION 12: Ecological information

12.1. Toxicity

Substance	Species	Test	Test duration	Result
cyclopentane	Fish	LC50	96 h	100000 ug/L

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
No data available.			

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BFC
No data available.			

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

This product contains ecotoxic substances which can have damaging effects on water-organisms. This product contains substances which can cause undesirable long-term effects in the water environment, due to its poor biodegradability.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The product is covered by the regulations on dangerous waste.

Waste

EWC code
160504

Specific labelling

-

Contaminated packing

Packaging which contains leftovers from the product must be disposed of in the same way as the product.

SECTION 14: Transport information

This product is covered by the conventions on dangerous goods.

14.1 – 14.4

ADR/RID

14.1. UN number	1950
14.2. UN proper shipping name	AEROSOLS, FLAMMABLE
14.3. Transport hazard class(es)	2.1
14.4. Packing group	II
Notes	-
Tunnel restriction code	D

IMDG

UN-no.	1950
Proper Shipping Name	AEROSOLS, FLAMMABLE

According to EC-Regulation 1907/2006 (REACH)

Class	2.1
PG*	II
EmS	F-D, S-U
MP**	-
Hazardous constituent	Cyclopentane, Heptane, Petroleum gas; liquefied

IATA/ICAO

UN-no.
Proper Shipping Name
Class
PG*

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 must not be exposed to this product cf. Council Directive 94/33/EC.

Demands for specific education

-

Additional information

Sources

EC regulation 1907/2006 (REACH)

Directive 2000/532/EC

EC Regulation 1272/2008 (CLP)

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H220 - Extremely flammable gas.

H225 - Highly flammable liquid and vapour.

H280 - Contains gas under pressure; may explode if heated.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

H412 - Harmful to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

-

Other symbols mentioned in section 2



Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

According to EC-Regulation 1907/2006 (REACH)

A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

The safety data sheet is validated by

MJH

**Date of last essential change
(First cipher in SDS version)**

-

**Date of last minor change
(Last cipher in SDS version)**

-

ALPHAOMEGA. Licens nr.:2830322911, ITW Chemical Products Scandinavia ApS
www.chymeia.com