



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Bergolin Härter 7D203

Revision date: 06.01.2025 Product code: A1012690 Page 1 of 13

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Bergolin Härter 7D203

Product group: Produkt

UFI: CWN7-EP1K-CC1M-H6CJ

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Hardener for 2K polyurethane systems

### Uses advised against

No information available.

# 1.3. Details of the supplier of the safety data sheet

Company name: Bergolin GmbH & Co. KG

Street: Sachsenring 1

Place: D-27711 Osterholz-Scharmbeck

Telephone: +49 4795 95899 0
e-mail: info@bergolin.de
Contact person: Gefahrstoffmanagement
e-mail: sdb@bergolin.de

Internet: www.bergolin.de

Responsible Department: Sicherheitsdatenblattverwaltung

**1.4. Emergency telephone** +49 4795 95899 0

number:

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### **Regulation (EC) No 1272/2008**

Acute Tox. 4; H332 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

# Regulation (EC) No 1272/2008

## Hazard components for labelling

Hexamethylene-1,6-diisocyanate homopolymer

aliphatic polyisocyanate hexamethylene-di-isocyanate

Signal word: Warning

Pictograms:



# **Hazard statements**

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Bergolin Härter 7D203

Revision date: 06.01.2025 Product code: A1012690 Page 2 of 13

H335 May cause respiratory irritation.

### **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

### Special labelling of certain mixtures

EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional

use.

# **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

#### Chemical characterization

Aliphatic Polyisocyanate

### **Hazardous components**

CAS No	Chemical name			Quantity	
	EC No	Index No	REACH No		
	Classification (Regulation (EC) No	1272/2008)			
28182-81-2	Hexamethylene-1,6-diisocyanate h	omopolymer		45 - < 50 %	
	500-060-2				
	Acute Tox. 4, Skin Sens. 1, STOT SE 3; H332 H317 H335				
185507-40-8	aliphatic polyisocyanate			45 - < 50 %	
	Acute Tox. 4, Eye Irrit. 2, Skin Sens	s. 1, STOT SE 3; H332 H319 H317 H	1335		
822-06-0	hexamethylene-di-isocyanate	hexamethylene-di-isocyanate			
	212-485-8				
	Acute Tox. 1, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT SE 3; H330 H302 H315 H319 H334 H317 H335				

Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity				
	Specific Conc. L	pecific Conc. Limits, M-factors and ATE					
28182-81-2	500-060-2	Hexamethylene-1,6-diisocyanate homopolymer	45 - < 50 %				
	1	ATE = 11 mg/l (vapours); inhalation: LC50 = 0,39 mg/l (dusts or mists); dermal: LD50 g/kg; oral: LD50 = >2500 mg/kg					
185507-40-8		aliphatic polyisocyanate	45 - < 50 %				
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg						
822-06-0	212-485-8	5-8 hexamethylene-di-isocyanate					
	inhalation: LC50 = 0,124 mg/l (vapours); inhalation: ATE = 0,005 mg/l (dusts or mists); dermal: LD50 = >7000 mg/kg; oral: LD50 = 959 mg/kg Resp. Sens. 1; H334: >= 0,5 - 100 Skin Sens. 1; H317: >= 0,5 - 100						

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

# **General information**

In all cases of doubt, or when symptoms persist, seek medical advice.



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

# Bergolin Härter 7D203

Revision date: 06.01.2025 Product code: A1012690 Page 3 of 13

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious place in recovery position and seek medical advice.

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### After inhalation

Remove casualty to fresh air and keep warm and at rest.

Call a doctor if you feel unwell.

In case of irregular breathing or respiratory arrest provide artificial respiration. Call a physician immediately.

#### After contact with skin

Take off immediately all contaminated clothing and wash it before reuse.

Wash with plenty of water/soap.

Do not wash with: Solvent/Thinner.

If skin irritation or rash occurs: Get medical advice/attention.

#### After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect).

Call a physician immediately.

Put victim at rest, cover with a blanket and keep warm.

Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

## 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam. Carbon dioxide. Powder. Water fog.

### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Danger of serious damage to health by prolonged exposure.

Use appropriate respiratory protection.

### 5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

In case of fire: Wear self-contained breathing apparatus. Special protective equipment for firefighters:

Protective equipment

### **Additional information**

Do not allow water used to extinguish fire to enter drains or waterways. Dispose of waste according to applicable legislation.

### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### **General advice**

Keep away from sources of ignition - No smoking. Ventilate affected area.

Avoid breathing dust/fume/gas/mist/vapours/spray.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Bergolin Härter 7D203

Revision date: 06.01.2025 Product code: A1012690 Page 4 of 13

Use personal protection equipment.

See protective measures under point 7 and 8.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### 6.3. Methods and material for containment and cleaning up

#### Other information

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

The contaminated area should be cleaned up immediately with:

a mixture of 45% water, 50% ethanol or isopropyl alcohol, 5% concentrated ammonia solution (density 0.880) (Flammable)

Other:

a mixture of 95% water and 5% sodium carbonate (Non-flammable.)

Add the decontaminant to the remnants and let stand for several days in a non-sealed container until no further reaction is observed. Once reaction is finished, close container and dispose of.

### 6.4. Reference to other sections

Disposal: see section 13

Personal protection equipment: see section 8

Safe handling: see section 7

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

People who suffer from asthma, allergies, chronic or recurring respiratory illnesses must not be deployed in processes, which use this substance. Examination of lung function should be carried out on a regular basis on persons spraying this product.

Avoid release to the environment. In use, may form flammable/explosive vapour-air mixture. Only use the material in places where open light, fire and other flammable sources can be kept away. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Provide earthing of containers, equipment, pumps and ventilation facilities. Use non-sparking tools. Wear antistatic work clothing.

Handle and open container with care. Reacts with: Water. moisture. Formation of: Carbon dioxide (CO2). Due to gaseous decomposition products, overpressure can occur in tightly sealed containers.

Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray. When using do not eat, drink or smoke. Wear personal protection equipment.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

### Advice on protection against fire and explosion

Vapours are heavier than air and will spread at floor level.

Vapours may form explosive mixtures with air.

# Advice on general occupational hygiene

Harmful dust is produced during dry-state pulverisation. Do not subject to grinding. (Avoid dust formation.) If possible, dampen before cutting or drilling. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Bergolin Härter 7D203

Revision date: 06.01.2025 Product code: A1012690 Page 5 of 13

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Draw up and observe skin protection programme.

Make available sufficient washing facilities

### Further information on handling

Conditions to avoid: Avoid contact with water. - Protect from moisture.

Carbon dioxide (CO2) (chemical identity of the evolved gas). Due to gaseous decomposition products, overpressure can occur in tightly sealed containers.

## 7.2. Conditions for safe storage, including any incompatibilities

### Hints on joint storage

Do not store together with: Oxidizing agents. amines. Alcohols. Water. Strong acid, strong alkalis

## Further information on storage conditions

Notice the directions for use on the label.

Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking.

Store in a place accessible by authorized persons only.

Always close containers tightly after the removal of product.

### 7.3. Specific end use(s)

No information available.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

## Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
822-06-0	Hexamethylene diisocyanate (as -NCO)	0.005	-		TWA (8 h)	

### **DNEL/DMEL values**

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
28182-81-2 Hexamethylene-1,6-diisocyanate homopolymer					
Worker DNEL,	acute	inhalation	local	1 mg/m³	
Worker DNEL, long-term		inhalation	local	0,5 mg/m³	
822-06-0 hexamethylene-di-isocyanate					
Worker DNEL, long-term		inhalation	local	0,035 mg/m³	
Worker DNEL,	acute	inhalation	local	0,07 mg/m³	



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Bergolin Härter 7D203

Revision date: 06.01.2025 Product code: A1012690 Page 6 of 13

#### **PNEC values**

CAS No	Substance	
Environmenta	al compartment	Value
28182-81-2 Hexamethylene-1,6-diisocyanate homopolymer		
Freshwater		0,127 mg/l
Freshwater s	ediment	266701 mg/kg
Marine sediment 26670 r		26670 mg/kg
Micro-organis	sms in sewage treatment plants (STP)	88 mg/l
Soil		53183 mg/kg
822-06-0	hexamethylene-di-isocyanate	
Micro-organis	sms in sewage treatment plants (STP)	8,42 mg/l

#### Additional advice on limit values

People who suffer from asthma, allergies, chronic or recurring respiratory illnesses must not be deployed in processes, which use this substance. Examination of lung function should be carried out on a regular basis on persons spraying this product.

# 8.2. Exposure controls

### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

## Individual protection measures, such as personal protective equipment

### Eye/face protection

Wear eye/face protection.

### Hand protection

Wear protective gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the wear time limits as specified by the manufacturer.

Suitable material: rubair búitileach nó Viton (is gá go mbeadh resistance ar an ábhar agus See information supplied by the manufacturer.)

Breakthrough time (maximum wearing time): \_\_\_\_min.

Use protective skin cream before handling the product.

#### Skin protection

Wear anti-static footwear and clothing (Natural fibres (e.g. cotton) / heat-resistant synthetic fibres)

# Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values

Provide adequate ventilation. Combination filtering device (EN 14387).

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Self-contained respirator (breathing apparatus) (DIN EN 133).

# **Environmental exposure controls**

Do not allow to enter into surface water or drains.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Bergolin Härter 7D203

Revision date: 06.01.2025 Product code: A1012690 Page 7 of 13

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: characteristic

Test method

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

>150 °C

boiling range:

Flash point: 62 °C DIN 53213

**Flammability** 

Solid/liquid: not determined
Gas: not determined

**Explosive properties** 

No information available.

Auto-ignition temperature: 360 °C

Self-ignition temperature

Solid: not determined
Gas: not determined
Decomposition temperature: not determined
pH-Value: not determined
Viscosity / dynamic: not determined
Viscosity / kinematic: not determined

Flow time: > 100 6 DIN EN ISO 2431

(at 23 °C)

Water solubility: not determined Partition coefficient n-octanol/water: not determined Vapour pressure: 0,03 hPa

(at 20 °C)

Vapour pressure: 0,21 hPa

(at 50 °C)

Density (at 20 °C): 1,13 g/cm³ DIN 53217

Relative vapour density: not determined

9.2. Other information

Sustaining combustion:

No data available

Oxidizing properties

No information available.

Solvent separation test: <3 % (ADR/RID)
Solid content: 100,00 %
Evaporation rate: not determined

**Further Information** 



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Bergolin Härter 7D203

Revision date: 06.01.2025 Product code: A1012690 Page 8 of 13

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Reacts with: Water. (Yes, slowly) Formation of: Carbon dioxide.

## 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Keep away from: Oxidizing agents. amines. Alcohols. Water. Strong acid, strong alkalis

Due to gaseous decomposition products, overpressure can occur in tightly sealed containers. Danger of bursting container.

### 10.4. Conditions to avoid

In case of warming: Thermal decomposition.

## 10.5. Incompatible materials

Exothermic reactions with: amines. Alcohols.

### 10.6. Hazardous decomposition products

Carbon monoxide Carbon dioxide. Nitrogen oxides (NOx).

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Harmful if inhaled.

#### **ATEmix tested**

	Dose	Species	Source
1050 : 1 1 (; / ) /41)	4.4 /1		

LC50, inhalation (vapour) (4 h) 11 mg/l LC50, inhalation (dust/mist) (4 h) 1,5 mg/l



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Bergolin Härter 7D203

Revision date: 06.01.2025 Product code: A1012690 Page 9 of 13

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
28182-81-2	Hexamethylene-1,6-diiso	cyanate hom	opolymer			
	oral	LD50 mg/kg	>2500	Rat		
	dermal	LD50 mg/kg	>2000	Rat		
	inhalation vapour	ATE	11 mg/l			
	inhalation (4 h) dust/mist	LC50	0,39 mg/l	Rat		OECD 403
185507-40-8	aliphatic polyisocyanate					
	oral	LD50 mg/kg	>2000	Rat		
	dermal	LD50 mg/kg	>2000	Rat		
	inhalation vapour	ATE	11 mg/l			
	inhalation dust/mist	ATE	1,5 mg/l			
822-06-0	hexamethylene-di-isocya	nate				
	oral	LD50 mg/kg	959	Rat		
	dermal	LD50 mg/kg	>7000	Rat		
	inhalation (4 h) vapour	LC50 mg/l	0,124	Rat		
	inhalation dust/mist	ATE mg/l	0,005			

### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Irritating to skin.

### Sensitising effects

Contains isocyanates. May produce an allergic reaction. May cause an allergic skin reaction.

(Hexamethylene-1,6-diisocyanate homopolymer; aliphatic polyisocyanate; hexamethylene-di-isocyanate)

People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this preparation.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

# STOT-single exposure

May cause respiratory irritation. (Hexamethylene-1,6-diisocyanate homopolymer; aliphatic polyisocyanate)

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

# **Aspiration hazard**

Based on available data, the classification criteria are not met.

Contains isocyanates. May produce an allergic reaction. Respiratory or skin sensitisation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

# **Practical experience**

Following inhalation:

May cause respiratory irritation. Potential hazards: Liver and kidney damage. Depression of the central nervous system. Symptoms: Headache. Dizziness. Causes drowsiness or dizziness. unconsciousness.

### After skin contact:



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Bergolin Härter 7D203

Revision date: 06.01.2025 Product code: A1012690 Page 10 of 13

The product is skin resorptive. Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Following eye contact:

Irritating to eyes. (reversible.)

# 11.2. Information on other hazards

#### Other information

Isocyanate containing product.

Respiratory or skin sensitisation/Irritant effect on the respiratory tract: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this preparation.

#### **Further information**

There are no data available on the preparation/mixture itself.

# **SECTION 12: Ecological information**

## 12.1. Toxicity

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
28182-81-2	Hexamethylene-1,6-diisoo	-diisocyanate homopolymer					
	Acute fish toxicity	LC50 mg/l	>=100	96 h	Brachydanio rerio (zebra-fish)		
	Acute algae toxicity	ErC50 mg/l	>1000		: Scenedesmus subspicatus		DIN 38412
	Acute crustacea toxicity	EC50	127 mg/l		Daphnia magna (Big water flea)		
	Acute bacteria toxicity	(EC50 mg/l)	3828	3 h	Activated sludge		OECD 209

# 12.2. Persistence and degradability

Some of the components are poorly biodegradable.

CAS No	Chemical name			
	Method Value d Source			
	Evaluation			
822-06-0	hexamethylene-di-isocyanate			
	OECD 301D	1%	28	

### 12.3. Bioaccumulative potential

No further relevant information available.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
28182-81-2	Hexamethylene-1,6-diisocyanate homopolymer	8,38

# BCF

CAS No	Chemical name	BCF	Species	Source
822-06-0	hexamethylene-di-isocyanate	367,7		

### 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

# Bergolin Härter 7D203

Revision date: 06.01.2025 Product code: A1012690 Page 11 of 13

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No information available.

#### **Further information**

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

### **Disposal recommendations**

Do not allow to enter into surface water or drains.

Remove according to the regulations.

Hazardous waste according to Directive 2008/98/EC (waste framework directive). The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### List of Wastes Code - residues/unused products

080501 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND

PRINTING INKS; wastes not otherwise specified in 08; waste isocyanates; hazardous waste

## Contaminated packaging

Completely emptied packages can be recycled.

Remove according to the regulations.

### **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.2. UN proper shipping name: No dangerous good in sense of this transport regulation.

### Other applicable information (land transport)

No dangerous good in sense of this transport regulation.

#### Marine transport (IMDG)

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

# Other applicable information (marine transport)

No dangerous good in sense of this transport regulation.

### Air transport (ICAO-TI/IATA-DGR)

<u>14.2. UN proper shipping name:</u> No dangerous good in sense of this transport regulation.

# Other applicable information (air transport)

No dangerous good in sense of this transport regulation.

# 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

# 14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

# 14.7. Maritime transport in bulk according to IMO instruments

not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Bergolin Härter 7D203

Revision date: 06.01.2025 Product code: A1012690 Page 12 of 13

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2010/75/EU (VOC):

0%

Information according to 2012/18/EU No

(SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

**Additional information** 

Observe in addition any national regulations!

#### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 8,15.

### Abbreviations and acronyms

ADR - Accord européen relatif transport des merchandises dangereuses par route ATE - Acute Toxicity Estimate / Schätzwert akuter Toxizität; BCF - Biokonzentrationsfaktor (Bio-Concentration Factor); CAS - Chemical Abstracts Service; CLP - Regulation on Classification, Labelling and Packaging of Substances and Mixtures; CMR - Carcinogenität, Mutagenität, Reproduktionstoxizität; ECHA - European Chemicals Agency / Europäische Chemikalienagentur (in Helsinki); EC50 - Effective Concentration 50%; ErC50 - Average specific growth rate; EINECS - European Inventory of Existing Commercial Chemical Substances; DNEL - "Derived No-Effect Level"; IATA - International Air Transport Association; IMDG - International Maritime Dangerous Goods Code; LC50 - Lethal Concentration 50%; LD50 - Lethal dose 50%; NOAEC/L - No Observed Adverse Effect Concentration / Level; NOEC - No Observed Effect Concentration; OECD - Organization for Economic Cooperation and Development; PBT - Persistent, Bioaccumulative, Toxic (persistent, bioakkumulativ, toxisch); PNEC - Predicted No Effect Concentration; REACH - Registration, Evaluation and Authorization of Chemicals; RID - Règlement International concernant le transport de marchandises dangereuses par chemin de fer; SCL - Specific Concentration Level; STOT - Specific Target Organ Toxicity; SVHC - Stoff sehr hoher Besorgnis (Substance of Very High Concern); VOC - Volatile Organic Compounds; WGK - Wassergefährdungsklasse

# Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H332	On basis of test data
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method

#### Relevant H and EUH statements (number and full text)

11302	Haiffidi II Swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms

Harmful if swallowed

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

EUH204 Contains isocyanates. May produce an allergic reaction.

H303



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Bergolin Härter 7D203

Revision date: 06.01.2025 Product code: A1012690 Page 13 of 13

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)