

SAFETY DATA SHEET

TRI-17 Olie med PTFE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

TRI-17 Olie med PTFE

Product no.

17105

Unique formula identifier (UFI)

W910-00M3-U001-SRRP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Lubricant

Use descriptors (REACH)

Product category	Description
PC24	Lubricants, Greases and Release Products

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

ITW Spraytec Nordic

Priorsvej 36

DK-8600 Silkeborg

Denmark

Tel: +45 86 82 64 44

E-mail

info@itw-spraytec.dk

Revision

25/11/2022

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2; H315, Causes skin irritation.

Eye Irrit. 2; H319, Causes serious eye irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)

Causes skin irritation. (H315)
 Causes serious eye irritation. (H319)
 May cause drowsiness or dizziness. (H336)
 Harmful to aquatic life with long lasting effects. (H412)

Safety statement(s)

General

-

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
 Do not spray on an open flame or other ignition source. (P211)
 Do not pierce or burn, even after use. (P251)
 Use only outdoors or in a well-ventilated area. (P271)
 Wear eye protection/protective gloves. (P280)

Response

-

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

Disposal

Dispose of contents/container in accordance with local regulation
 . (P501)

Hazardous substances

Naphtha (petroleum), hydrotreated light (<0,1 % w/w benzene (EINECS No 200-753-7)).

Additional labelling

UFI: W910-00M3-U001-SRRP

2.3. Other hazards

Additional warnings

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.
 This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.
 This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Naphtha (petroleum), hydrotreated light (<0,1 % w/w benzene (EINECS No 200-753-7)).	CAS No.: 64742-49-0 EC No.: 265-151-9 UK-REACH: Index No.: 649-328-00-1	15-25%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	[15], [19]
Propane	CAS No.: 74-98-6 EC No.: 200-827-9 UK-REACH: Index No.: 601-003-00-5	10-15%	Flam. Gas 1A, H220	
Butane (<0,1 % w/w 1,3-butadiene)	CAS No.: 106-97-8 EC No.: 203-448-7 UK-REACH: Index No.: 601-004-00-0	5-10%	Flam. Gas 1A, H220	
Isobutane	CAS No.: 75-28-5 EC No.: 200-857-2 UK-REACH: Index No.: 601-004-00-0	3-5%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	CAS No.: 4259-15-8 EC No.: 224-235-5 UK-REACH: Index No.:	1-3%	Eye Dam. 1, H318 (SCL: 50.00 %) Aquatic Chronic 2, H411	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[15] The classification as a carcinogen / mutagen will not be taken into account as the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7) (CLP, Annex VI, note P).

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 5 minutes and continue until irritation stops. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs.

Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Sulphur oxides

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

Recommended storage material

Keep only in original packaging.

Storage temperature

< 50°C

Protected from direct sunlight.

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Butane (<0,1 % w/w 1,3-butadiene)

Long term exposure limit (8 hours) (ppm): 600

Long term exposure limit (8 hours) (mg/m³): 1450

Short term exposure limit (15 minutes) (ppm): 750

Short term exposure limit (15 minutes) (mg/m³): 1810

Annotations:

Carc1 = Capable of causing cancer and/or heritable genetic damage if it contains more than 0.1% of buta-1,3-diene.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.

EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

Naphtha (petroleum), hydrotreated light (<0,1 % w/w benzene (EINECS No 200-753-7)).

Duration	Route of exposure	DNEL
----------	-------------------	------

PNEC

No data available.

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

Provide adequate general and local exhaust ventilation.

8.3. Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

In case of insufficient ventilation a respirator with combination filter A2/P2 is recommended.

Skin protection

No special requirements.

Hand protection

Gloves are usually not required. In case of prolonged or repeated skin contact, Nitrile gloves are recommended.

Eye protection

Wear safety goggles if there is a risk of eye splash.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Aerosol

Colour

White

Odour / Odour threshold

Characteristic

pH

No data available

Density (g/cm³)

No data available

Relative density

No data available

Kinematic viscosity

No data available

Particle characteristics

No data available

Phase changes

Melting point/Freezing point (°C)

No data available

Softening point/range (waxes and pastes) (°C)

Does not apply to aerosols.

Boiling point (°C)

No data available

Vapour pressure

No data available

Relative vapour density

No data available

Decomposition temperature (°C)

No data available

Data on fire and explosion hazards

Flash point (°C)

<-100

Auto-Ignition (°C)

No data available

Flammability (°C)

No data available

Lower and upper explosion limit (% v/v)

No data available

Solubility

Solubility in water

Completely soluble

n-octanol/water coefficient

No data available

Solubility in fat (g/L)

No data available

9.2. Other information

Evaporation rate (n-butylacetate = 100)

No data available

Other physical and chemical parameters

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance Naphtha (petroleum), hydrotreated light (<0,1 % w/w benzene (EINECS No 200-753-7)).

Test method

Species

Rat

Route of exposure

Oral

Test

LD50

Result

> 5000 mg/kg ·

Other information

Product/substance

Naphtha (petroleum), hydrotreated light (<0,1 % w/w benzene (EINECS No 200-753-7)).

Test method

Species

Rabbit

Route of exposure

Dermal

Test

LD50

Result

> 2000 mg/kg ·

Other information

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

None known.

Other information

None known.

SECTION 12: Ecological information

12.1. Toxicity

No data available.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

Product/substance Butane (<0,1 % w/w 1,3-butadiene)

Test method

Potential bioaccumulation No

LogPow 2,8900

BCF No data available.

Other information

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

None known.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

Waste treatment methods

Product is not covered by regulations on dangerous waste.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

16 05 04* Gases in pressure containers (including halons) containing dangerous substances



Specific labelling

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
ADR	UN1950	AEROSOLS	Class: 2 Labels: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L Tunnel restriction code: (D) See below for additional information.
IMDG	UN1950	AEROSOLS	Class: 2 Labels: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L EmS: F-D S-U See below for additional information.
IATA	UN1950	AEROSOLS	Class: 2 Labels: 2.1 Classification code: 5F 	-	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)

Additional information

Not applicable.

Sources

The Aerosol Dispensers Regulations 2009 No. 2824, amended in 2014 (No. 1130) and in 2018 (No. 29).

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H220, Extremely flammable gas.
H225, Highly flammable liquid and vapour.
H280, Contains gas under pressure; may explode if heated.
H304, May be fatal if swallowed and enters airways.
H315, Causes skin irritation.
H318, Causes serious eye damage.
H336, May cause drowsiness or dizziness.
H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

PC24 = Lubricants, Greases and Release Products

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

MJH

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en