

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ALEXIT BR1232 BladeRep Topcoat 12 RAL 3020 verkehrsrot
/ traffic red matt / matte

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Industrial serial painting
stance/Mixture

1.3 Details of the supplier of the safety data sheet

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Strasse 189
21107 Hamburg
Germany

Only for UK:

Supplied by Mankiewicz UK LLP
26 Ashville Way, Whetstone,
Leicester LE8 6NU
United Kingdom

Telephone +49 (0) 40 75103 0
E-mail address of person sdb_info@umco.de
responsible for the SDS

1.4 Emergency telephone number

Emergency telephone num- : +44 1865 407333 (NCEC)
ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements :
H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapours.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.

Hazardous components which must be listed on the label:

n-butyl acetate

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

Toxicological information: This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f),

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture of synthetic resins, organic solvents and pigments

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 12.5 - < 20
Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics	128601-23-0 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066 EUH066	>= 12.5 - < 20
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 01-2119491304-40	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2.5
reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxy-phe-nyl)propionyloxypoly(oxyethylene)	Not Assigned 400-830-7 607-176-00-3 01-0000015075-76	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 0.5 - < 1
propylidynetrimethanol	77-99-6 201-074-9 01-2119486799-10	Repr. 2; H361fd	>= 0.25 - < 0.5

These contain:

butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318	>= 0 - < 0.1
------------	--	---	--------------

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
USt-IdNr.: DE 118241333

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDE3300
PBNKDE3300
HYVEDE3300

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

		STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system)	
--	--	--	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In all cases of doubt, or when sickness symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air, keep patient warm and at rest.
Irregular breathing/no breathing: artificial respiration.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognised skin cleanser.
Do NOT use solvents or thinners !
- In case of eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- If swallowed : Do NOT induce vomiting.
If accidentally swallowed obtain immediate medical attention.
Never give anything by mouth to an unconscious person.
Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause an allergic skin reaction.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol resistant foam, CO2, powders
- Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters : Appropriate breathing apparatus may be required.

Further information : Cool endangered containers with water in case of fire.
DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO ENTER DRAINS OR WATER COURSES!!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Exclude sources of ignition and ventilate the area.
Do not inhale vapours.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Do not let product enter drains.
If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see chapter 13).
Clean preferably with a detergent; avoid use of solvents.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.
Comply with the health and safety at work laws.
Smoking, eating and drinking should be prohibited in the application area.
Observe specific national regulations for handling and use of paints.

Advice on protection against fire and explosion : The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing. No sparking tools should be used. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage.
- Further information on storage conditions : Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep container dry in a cool, well-ventilated place.
- Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.
- Recommended storage temperature : 5 - 35 °C

7.3 Specific end use(s)

- Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	TWA	150 ppm 724 mg/m ³	GB EH40
		STEL	200 ppm 966 mg/m ³	GB EH40
		STEL	150 ppm 723 mg/m ³	2019/1831/EU
	Further information: Indicative			
		TWA	50 ppm 241 mg/m ³	2019/1831/EU
	Further information: Indicative			
butan-1-ol	71-36-3	STEL	50 ppm 154 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m3
	Workers	Dermal	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	35.7 mg/m3
	Consumers	Dermal	Long-term systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics	Workers	Inhalation	Long-term systemic effects	150 mg/m3
	Workers	Dermal	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	32 mg/m3
	Consumers	Dermal	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	11 mg/kg bw/day
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Workers	Inhalation	Long-term systemic effects	1.27 mg/m3
	Workers	Dermal	Long-term systemic effects	1.8 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.31 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.9 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.18 mg/kg bw/day
reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxy-phenyl)propionyl-omega-hydroxy-poly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxy-phenyl)propionyl-omega-3-(3-(2H-	Workers	Inhalation	Long-term systemic effects	0.398 mg/m3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)				
	Workers	Dermal	Long-term systemic effects	0.25 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.099 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.025 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.025 mg/kg bw/day
propylidynetrimethanol	Workers	Inhalation	Long-term systemic effects	3.3 mg/m3
	Workers	Dermal	Long-term systemic effects	0.94 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.58 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.34 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.34 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
n-butyl acetate	Fresh water	0.18 mg/l
	Marine water	0.018 mg/l
	Fresh water sediment	0.981 mg/kg dry weight (d.w.)
	Marine sediment	0.098 mg/kg dry weight (d.w.)
	Sewage treatment plant	35.6 mg/l
	Soil	0.09 mg/kg dry weight (d.w.)
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Fresh water	0.002 mg/l
	Marine water	0 mg/l
	Sewage treatment plant	1 mg/l
	Fresh water sediment	1.05 mg/kg dry weight (d.w.)
	Marine sediment	0.11 mg/kg dry weight (d.w.)
	Soil	0.21 mg/kg dry weight (d.w.)
reaction mass of a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and a-3-(3-(2H-benzotriazol-2-yl)-5-tert-	Fresh water	0.023 mg/l

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Gau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Gau
UST-IdNr.: DE 118241333

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDE3300
PBNKDE3300
HYVEDE3300

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

butyl-4-hydroxyphenyl)propionyl- omega-3-(3-(2H-benzotriazol-2- yl)-5-tert-butyl-4- hydroxy- phe- nyl)propionyloxypoly(oxyethylene)		
	Marine water	0 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	7.26 mg/kg dry weight (d.w.)
	Marine water	0.726 mg/kg dry weight (d.w.)
	Soil	14.52 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain aerosol- and solvent vapours concentration below the OEL, suitable respiratory protection must be worn.

Personal protective equipment

Eye/face protection : Wear safety goggles to protect against solvent splashes.

Hand protection

Remarks : Adhere to the professional organisation rule "Use of protective gloves". Appropriate chemicals resistant glove tested in compliance with EN 374.
Recommendation for protection against components generally found in the products:

For short-term contact (i.e. splash protection):

Appropriate material:

nitrile rubber, Neoprene

Material thickness: > 0,4 mm

Breakthrough time: > 480 min

Before use, the protective glove should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Preventive hand protection (skin protection cream) recommended. Wash immediately contaminated skin. Design operations thus to avoid permanent use of protective gloves.

Skin and body protection : Depending on the probability of the occurrence of dangerously explosive atmospheres, adapted protective clothing must be worn.

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
UST-IdNr.: DE 118241333

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDE3300
PBNKDE3300
HYVEDE3300

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

- Respiratory protection : If the solvent concentration is above the air limit values, a breathing apparatus approved for this purpose must be worn. Use half-mask model with cartridge or air-fed. Dry grinding, torch cutting and/or welding however can produce hazardous dust and/or vapour. If possible, machine employing a wet medium. Where practicable, install exhaust hoods to improve capture of vapours and fumes and avoid exposition; otherwise wear respiratory protection equipment.
- Protective measures : Do not eat or drink during work - no smoking. Avoid product contact with skin, eyes and clothing. Avoid the inhalation of dust from sanding, particulates and spray mist arising from the application of this preparation. When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid (20 - 25 °C, 1,013 hPa)
- Colour : according product name
- Odour : characteristic
- Melting point/ range : No data available
- Upper explosion limit : 10 %(V)
- Lower explosion limit : 1 %(V)
- Flash point : 34 °C
Method: ISO 13736
- Auto-ignition temperature : > 400 °C
- Decomposition temperature : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

pH	:	6 - 8 (20 °C) Concentration: 10 %
Viscosity	:	
Viscosity, kinematic	:	> 21 mm ² /s
Flow time	:	> 150 s Cross section: 4 mm Method: DIN 53211
	:	> 100 s Cross section: 6 mm Method: ISO 2431
Solubility(ies)	:	
Water solubility	:	insoluble
Vapour pressure	:	ca. 100 hPa (50 °C)
Relative density	:	No data available
Density	:	ca. 1.4 g/cm ³ (20 °C)

9.2 Other information

Flammability (liquids)	:	No data available
Miscibility with water	:	immiscible
Solvent separation	:	< 3 %(V)

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	No dangerous reaction known under conditions of normal use. There are no data available on the preparation itself.
---------------------	---	---

10.4 Conditions to avoid

Conditions to avoid	:	Stable under recommended storage and handling conditions
---------------------	---	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

(See section 7).

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Grau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
USt-IdNr.: DE 118241333

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDE3300
PBNKDE3300
HYVEDE3300

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for human health according to UK REACH Article 57(f),

Further information

Product:

Remarks : Exposure of vapour concentration in excess of the stated OEL's may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue muscular weakness, drowsiness and in extrem cases, loss of consciousness.
Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : There are no data available on the preparation itself.

Components:

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.97 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 20 mg/l
aquatic invertebrates
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Desmodesmus subspicatus (green algae)): 1.68 mg/l
plants
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: The product has low solubility in the test medium. An aqueous dispersion was tested.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: The product has low solubility in the test medium. An aqueous dispersion was tested.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: There are no data available on the preparation itself.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: There are no data available on the preparation itself.

12.4 Mobility in soil

Product:

Mobility : Remarks: There are no data available on the preparation itself.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Assessment : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

12.7 Other adverse effects

Product:

Additional ecological information : There are no data available on the preparation itself.

The product should not be allowed to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1263

IMDG : UN 1263

IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT

IMDG : PAINT
(Hydrocarbon, C9, aromatics, Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate)

IATA : PAINT

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADR

Packing group : III

Classification Code : F1

Hazard Identification Number : 30

Labels : 3

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Gau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Gau
UST-IdNr.: DE 118241333

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDEMM300
PBNKDEFF200
HYVEDEMMXXX

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

Tunnel restriction code : (D/E)
Remarks : If transported within the user's premises: To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Gau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Gau
USt-IdNr.: DE 118241333

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDEMM300
PBNKDEFF200
HYVEDEMMXXX

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Volatile organic compounds :

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 32.79 %, 460 g/l

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for the mixture.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H361f	: Suspected of damaging fertility.
H361fd	: Suspected of damaging fertility. Suspected of damaging the unborn child.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Gau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Gau
USt-IdNr.: DE 118241333

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDE33000
PBNKDE33000
HYVEDE33000

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

Full text of other abbreviations

Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : The information given in this material safety data sheet does not release the user from its duty of risk assessment and control in the work place defined in other health and safety law.

Mankiewicz Gebr. & Co.
(GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg, Germany
T +49 40 751030
E info@mankiewicz.com

Sitz/Registriergericht Hamburg: HRA 42442
Persönlich haftende Gesellschafterin:
Gau Gebr. Beteiligungs-GmbH
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau
USt-IdNr.: DE 118241333

Bank
Deutsche Bank
HypoVereinsbank
Postbank
HypoVereinsbank USD

BIC
DEUTDE33XXX
HYVEDE33XXX
PBNKDE33XXX
HYVEDE33XXX

IBAN
DE58 2007 0000 0600 2273 00
DE34 2003 0000 0059 2733 00
DE85 2001 0020 0000 3732 05
DE33 7002 0270 0910 0501 52

www.mankiewicz.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Commercial Product Name: ALEXIT BR1232 BladeRep Topcoat 12
Quality No.: 471433020W000

Revision Date 31.01.2025
Print Date 31.01.2025
Version 4

Adhere to the national sanitary and occupational safety regulations when using this product.

This safety datasheet complies with the requirements of regulation (EC) No 1907/2006(2020/878).

Classification of the mixture:

Flam. Liq. 3	H226
Skin Sens. 1	H317
STOT SE 3	H336
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

Department issuing safety data sheet

UMCO GmbH
Georg-Wilhelm-Str.187, D-21107 Hamburg
Telefon: +49(0)40/555 546 300 Fax: +49(0)40/555 546 357
e-mail:umco@umco.de

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN